




機器學習演算法：從基礎理論到進階應用

核心機制、決策邏輯與模型優化實務指南



人工智慧的技術層次



機器學習的核心運作與預測類型



迴歸 (Regression)

預測結果為「連續數值」。



分類 (Classification)

預測結果為「類別」。




線性模型的數學解構

$$y = ax + b$$

預測值 (Prediction)

特徵 (Feature)

模型參數 (Parameters)




訓練目標：找到最佳的 a 與 b 。

殘差 (Residual)：真實值與預測值的差距 (每個點的預測誤差)。

損失函數 (Loss Function)：衡量整體誤差大小。常用平方和： $L = \sum e_i^2$ 。殘差越大，損失越大。

機器如何學習：梯度下降優化



1. 損失函數

$$f(x) = x^2$$

描述模型預設值與真實值的誤差。U型曲線越低，表示誤差越小。

2. 計算梯度

$$df/dx = 2x$$

告訴我們「下降最快的方向」。

← $x < 0$ → 梯度為負 → 往右更新。

→ $x > 0$ → 梯度為正 → 往左更新。

3. 核心思想

從初始值出發，沿梯度方向一步步更新 x ，重複直到梯度 = 0，找到最小值 (最低點)。

實務案例：主軸預壓力預測設定

7支相同規格、型號主軸，對應不同的預壓力 [N]。每支運轉1小時 (3600秒)，每2秒切段訊號做FFT，取得軸承內外環的振動量 [g]。


特徵 X (0.21g, 0.11g) → 類別 Y (主軸1)
...共1800筆。

特徵 X (0.32g, 0.14g) → 類別 Y (主軸2)
...共1800筆。


Actionable Questions

- ✓ 特徵是什麼？
(振動量)
- ✓ 輸出是什麼？
(預壓力)
- ✓ 這是迴歸問題，還是分類問題？

從數據看見特徵：迴歸與分類的轉換




迴歸問題(連續數值)：
120N, 680N, 890N... 2500N.



決策樹 (Decision Tree)

透過條件分割建立 非線性分類模型

Data & Principles



條件式分割

將資料集不斷分割，最終形成清晰的樹狀結構。


最佳分割點

在每個節點優先選擇「效益最大」的特徵進行切割。

特徵重用性

在不同的決策路徑中，同一個特徵可以被重複使用。

Tree Anatomy




實戰演練：從特徵推演決策路徑 與測試集準確度評估

1. 簡化版資料集

編號	年紀	收入	身高	結果
1	小	高	高	見面
2	小	高	矮	見面
3	小	高	高	見面
4	小	高	高	見面
5	小	高	矮	見面
6	大	低	矮	不見
7	大	低	矮	不見
8	小	低	矮	不見
9	大	低	矮	不見
10	小	低	高	不見

2. 決策路徑



3. 測試集評估

	預測比數	
	預測見面	預測不見
實際見面	5	0
	2	3

準確度 80%

集成學習：隨機森林 (Random Forest)

Mechanism 1: 自助抽樣法 Bootstrapping

對資料集 X (長度 n) 取後放回抽樣 n 次。

被抽中機率 $1/n$ ，沒被抽中機率 $1 - 1/n$ 。

$$\lim_{n \rightarrow \infty} \left(1 - \frac{1}{n}\right)^n = e^{-1} \approx 0.368$$



Mechanism 2 & 3: 弱分類器到強預測

弱化每棵決策樹的分類能力 (限制特徵)。

整合所有樹 ($C_1, C_2 \dots C_L$) 的結果

($\hat{Y}_1, \hat{Y}_2 \dots \hat{Y}_L$) 進行最終預測。




進階集成：極限提升樹 (XGBoost)

集合多個「弱分類器」成為一個「強分類器」(Ensemble Learning)


隨機森林 (Random Forest)：

弱分類器之間是不相關的(獨立投票)。



XGBoost (Boosting)：

弱分類器之間是相關的。



線性分類器：支持向量機 (SVM)

$$w^T x + b = 1$$

$$w^T x + b = 0 \text{ (Decision Boundary)}$$


$$w^T x + b = -1$$

Optimization Goal

在拘束條件下尋找參數 w 和 b ，使得兩類別之間的「距離 (Margin) 最大化」。


$$\min \frac{1}{2} w^T w + C \sum_{i=1}^n \xi_i$$

$$\text{Subject to: } y_i(w^T x_i + b) \geq 1 - \xi_i, \xi_i \geq 0$$




單類別分類：SVDD 異常偵測

- 單類別分類 (One-Class Classification)：從 SVM 延伸的演算法。
- 訓練邏輯：只使用「單一類別」的資料來訓練模型。
- 模型產出：學到「正常資料的分布範圍」。
- 應用場景：偵測異常或離群點 (Anomaly/Outlier Detection)。



在高維空間中，原本難以區分的資料點會變得更加分散，
線性分類器因此更容易將不同類別分開 ($w^T x + b = 0$)。



課程總結：機器學習演算法矩陣

基礎機制 (Foundations)

線性模型 & 梯度下降

尋找最低誤差的 a, b

資訊熵

降低資料雜亂度

樹狀邏輯 (Tree Ensembles)

決策樹

非線性條件分割

隨機森林

平行獨立、自助抽樣

XGBoost

序列相依、錯誤修正

邊界優化 (Boundary Optimizers)

SVM

最大化類別間距


SVDD

定義正常範圍，偵測異常

迴歸預測連續數值，分類預測離散類別。選擇演算法取決於資料特性、維度與實務目標。

無程式碼數據分析： Orange Data Mining 完全指南

以決策樹演算法 (Decision Tree) 為
例 —— 從資料輸入到模型解析



視覺化程式設計


拖曳小工具 (Widgets) 至畫布並建立連結，完全無需編寫程式碼即可構建分析流程。

互動式探索

資料的任何變更與篩選，皆會即時反映在視覺化圖表中。

開源與免費

由盧布爾雅那大學 (University of Ljubljana) 開發，支援 Windows, Mac OS 等多平台，為全球社群提供免費支援。



傳統資料科學

01

技術門檻：需精通 Python 或 R 語言，學習曲線陡峭。

02

分析過程：大量隱藏的腳本與變數，難以直觀除錯。

03

知識傳遞：難以向非技術領域的專家或學生展示邏輯推演過程。

Orange Data Mining



技術門檻：**零程式碼基礎**，直覺的拖曳介面。



分析過程：以「**視覺化工作流**」呈現，資料流向一目了然。



知識傳遞：極佳的跨領域溝通與教學工具，所見即所得。

捨棄繁瑣語法，專注於商業邏輯與決策

Python Scikit-learn

```
import pandas as pd
from sklearn.tree import DecisionTreeClassifier
data = pd.read_csv('data.csv')
X = data.drop('target', axis=1)
y = data['target']
model = DecisionTreeClassifier()
model.fit(X, y)

predictions = model.predict(X_test)
```

高學習門檻、需處理語法錯誤

Orange Data Mining 視覺化工作流



零程式碼、拖曳即完成建模

相同的機器學習預測能力，只需不到十分之一的建置時間。

構建完整的資料科學 workflows



從單一決策樹到複雜的交叉驗證，
Orange Data Mining 讓每一次的資料
分析都像拼圖一樣直觀且充滿樂趣。

Step 1 : 開啟 Orange Data Mining 介面

The image shows the Orange Data Mining software interface. The main window is titled "Untitled - Orange" and has a menu bar with "File", "Edit", "View", "Widget", "Window", "Options", and "Help". On the left is a widget palette with a search bar "Filter..." and categories: "Data", "Transform", "Visualize", "Model", and "Evaluate". The "Evaluate" category is selected, showing widgets like "Test and Score", "Predictions", "Feature as Predictor", "Confusion Matrix", "ROC Analysis", "Performance Curve", "Calibration Plot", and "Permutation Plot". Below the palette, it says "Select a widget to show its description." and provides links: "See [workflow examples](#), [YouTube tutorials](#), or open the [welcome screen](#)." At the bottom is a toolbar with icons for file operations and a help icon.

Overlaid on the main window is a "Welcome to Orange" dialog box. It contains buttons for "New", "Open", "Recent", "Video Tutorials", "Get Started", "Examples", and "Documentation". At the bottom of the dialog, there is a checkbox "Show at startup" which is checked, and a "Donate" link.

Filter...

Data

File CSV File Import Datasets SQL Table

Data Table Paint Data Data Info Rank

Edit Domain Color Column Statistics Save Data

Transform

Visualize

Model


Evaluate

Unsupervised

File

Read data from an input file or network and send a data table to the output.

[more...](#)



File - Orange

Source

File: datasets\iris.tab

URL:

File Type

Determine

Info

Iris flower dataset 鳶尾花資料集

Classical dataset with 150 instances of Iris setosa, Iris virginica and Iris versicolor.

150 instances 150 筆資料

4 features (no missing values) 4 個特徵，無缺失值

Classification; categorical class with 3 values (no missing values) 3 種類別的類別型資料

0 meta attributes 0 項「存在資料裡，但不會被模型拿來訓練的欄位」

Columns (Double click to edit)

	Name	Type	Role	Values
1	sepal length	N numeric	feature	
2	sepal width	N numeric	feature	
3	petal length	N numeric	feature	
4	petal width	N numeric	feature	
5	iris	C categorical	target	Iris-setosa, Iris-versicolor, Iris-virginica

Reset Apply

Browse documentation datasets

150

Filter...

Data

File CSV File Import Datasets SQL Table

Data Table Paint Data **Data Info** Rank

Edit Domain Color Column Statistics Save Data

Transform

Visualize


Model

Evaluate

Unsupervised

Data Info

Display basic information about the data set

[more...](#)

Data Info - Orange

Data table properties

Name: iris 鳶尾花資料集

Size: ~150 rows, 5 columns 150 列、5 行

Features: 4 numeric 4 個數值型特徵

Targets: categorical outcome with 3 classes 具有三種類別的類別型目標

Missing data: none 無缺失值

Additional attributes

Name: Iris flower dataset

Description: Classical dataset with 150 instances of Iris setosa, Iris virginica and Iris versicolor.

Author: Edgar Anderson, Ronald Fisher

Year: 1936

Reference: R. A. Fisher (1936). "The use of multiple measurements in taxonomic problems". Annals of Eugenics. 7 (2): 179–188. doi:10.1111/j.1469-1809.1936.tb02137.x

150

Filter...

Data

File CSV File Import Datasets SQL Table

Data Table Paint Data Data Info Rank

Edit Domain Color Column Statistics Save Data

Transform

Visualize

Model


Evaluate

Unsupervised

Data Table

View the dataset in a spreadsheet.

[more...](#)



Data Table - Orange

Info
150 instances (no missing data)
4 features
Target with 3 values
No meta attributes.

Variables
☒ Show variable labels (if present)
☐ Visualize numeric values
☒ Color by instance classes

Selection
Clear Selection
☒ Select full rows

Restore Original Order
☒ Send Automatically

	iris	sepal length	sepal width	petal length	petal width
1	Iris-setosa	5.1	3.5	1.4	0.2
2	Iris-setosa	4.9	3.0	1.4	0.2
3	Iris-setosa	4.7	3.2	1.3	0.2
4	Iris-setosa	4.6	3.1	1.5	0.2
5	Iris-setosa	5.0	3.6	1.4	0.2
6	Iris-setosa	5.4	3.9	1.7	0.4
7	Iris-setosa	4.6	3.4	1.4	0.3
8	Iris-setosa	5.0	3.4	1.5	0.2
9	Iris-setosa	4.4	2.9	1.4	0.2
10	Iris-setosa	4.9	3.1	1.5	0.1
11	Iris-setosa	5.4	3.7	1.5	0.2
12	Iris-setosa	4.8	3.4	1.6	0.2
13	Iris-setosa	4.8	3.0	1.4	0.1
14	Iris-setosa	4.3	3.0	1.1	0.1
15	Iris-setosa	5.8	4.0	1.2	0.2
16	Iris-setosa	5.7	4.4	1.5	0.4
17	Iris-setosa	5.4	3.9	1.3	0.4
18	Iris-setosa	5.1	3.5	1.4	0.3
19	Iris-setosa	5.7	3.8	1.7	0.3

150 150 | 150

Filter...

Data

File CSV File Import Datasets SQL Table

Data Table Paint Data Data Info Rank

Edit Domain Color **Column Statistics** Save Data

Transform

Visualize



Model

Evaluate

Unsupervised

Column Statistics

Show basic statistics for columns.

[more...](#)

Filter...

Data

Transform

Visualize

Tree Viewer

Box Plot

Violin Plot

Distributions

Scatter Plot

Line Plot

Bar Plot

Sieve Diagram

Mosaic Display

FreeViz

Linear Projection

Radviz

Heat Map

Venn Diagram

Silhouette Plot

Pythagorean Tree

Pythagorean Forest

CN2 Rule Viewer

Nomogram

Scoring Sheet Viewer

Model



Evaluate

Unsupervised

Box Plot

Visualize the distribution of feature values in a box plot.

[more...](#)



Step 8 : 資料分布分析 Distribution (分布圖)

Filter...

Data

Transform

Visualize

Tree Viewer

Box Plot

Violin Plot

Distributions

Scatter Plot

Line Plot

Bar Plot

Sieve Diagram

Mosaic Display

FreeViz

Linear Projection

Radviz

Heat Map

Venn Diagram

Silhouette Plot

Pythagorean Tree

Pythagorean Forest

CN2 Rule Viewer

Nomogram

Scoring Sheet Viewer

Model



Evaluate

Unsupervised

Distributions

Display value distributions of a data feature in a graph.

[more...](#)



Step 9 : 特徵關係視覺化 Scatter Plot (散佈圖)

Filter...

Data

Transform

Visualize

Tree Viewer Box Plot Violin Plot Distributions

Scatter Plot Line Plot Bar Plot Sieve Diagram

Mosaic Display FreeViz Linear Projection Radviz

Heat Map Venn Diagram Silhouette Plot Pythagorean Tree

Pythagorean Forest CN2 Rule Viewer Nomogram Scoring Sheet Viewer

Model



Evaluate

Unsupervised

Scatter Plot

Interactive scatter plot visualization with intelligent data visualization enhancements.

[more...](#)



Filter...

Data

Transform

Select Rows

Data Sampler

Select Columns

Transpose

Split

Merge Data

Concatenate

Select by Data Index

Unique

Aggregate Columns

Group by

Pivot Table

Apply Domain

Preprocess

Impute

Continuize

Discretize

Randomize

Purge Domain

Melt

Formula

Create Class

Create Instance


Python Script

Visualize

Model

Select a widget to show its description.

See [workflow examples](#), [YouTube tutorials](#), or open the [welcome screen](#).



Select Rows - Orange

Conditions

iris is not Iris-virginica

Add Condition Add All Variables Remove All

☐ Remove unused values and constant features

☐ Remove unused classes

☒ Send Automatically

150 100 50 150

Filter...

Data

Transform

Select Columns

Data Sampler

Select Rows

Transpose

Split

Merge Data

Concatenate

Select by Data Index

Unique

Aggregate Columns

Group by

Pivot Table

Apply Domain

Preprocess

Impute

Continuize

Discretize

Randomize

Purge Domain

Melt

Formula

Create Class

Create Instance

Python Script


Visualize

Model

Select Columns

Select columns from the data table and assign them to data features, classes or meta variables.

[more...](#)



Select Columns - Orange

Ignored

Filter

Features (4)

Filter

- N petal length
- N petal width
- N sepal length
- N sepal width

Target (1)

C iris


Metas

Reset

☐ Ignore new variables by default

☒ Send Automatically

150 | - 150 | 4



Randomly draw a subset of data points from the input dataset.

[more...](#)

Filter...

Data

Transform

Visualize

Model

Constant

CN2 Rule Induction

Calibrated Learner

kNN

Tree

Random Forest

Gradient Boosting

SVM

Linear Regression

Logistic Regression

Naive Bayes

Scoring Sheet

AdaBoost

PLS

Curve Fit

Neural Network

Stochastic Gradient D...

Stacking

Save Model

Load Model


Evaluate

Unsupervised

Tree

A tree algorithm with forward pruning.

[more...](#)



Step 14 : 理解模型規則 Decision Tree 視覺化

教學2.ows* - Orange

File Edit View Widget Window Options Help

Filter...

Data

Transform

Visualize

Tree Viewer

Box Plot

Violin Plot

Distributions

Scatter Plot

Line Plot

Bar Plot

Sieve Diagram

Mosaic Display

FreeViz

Linear Projection

Radviz

Heat Map

Venn Diagram

Silhouette Plot

Pythagorean Tree

Pythagorean Forest

CN2 Rule Viewer

Nomogram

Scoring Sheet Viewer


Model

Evaluate


Unsupervised

Tree Viewer

[more...](#)



控制樹的深度



Step 15 : 模型評估方法 Test & Score (Cross Validation, 交叉驗證)

The screenshot displays the Orange3 data mining software interface. On the left, the widget toolbox is visible, with the 'Test and Score' widget highlighted by a red box. The main workspace shows a workflow: 'Data' (File) -> 'Data Sampler' -> 'Tree' (Learner) -> 'Tree Viewer' and 'Test and Score' -> 'Confusion Matrix'. The 'Test and Score' widget is also highlighted with a red box. A red arrow points from the 'Test and Score' widget in the workflow to the 'Test and Score - Orange' settings window. Another red arrow points from the 'Test and Score' widget to the evaluation results table in the settings window.

Test and Score - Orange Settings

交叉驗證，5 折交叉驗證。

☒ Cross validation
Number of folds: 5
☒ Stratified

☐ Cross validation by feature
☐ Random sampling
Repeat train/test: 20
Training set size: 66 %
☒ Stratified
☐ Leave one out
☐ Test on train data
☐ Test on test data

Evaluation results for target (None, show average over classes)



Model	AUC	CA	F1	Prec	Recall	MCC
Tree	0.972	0.933	0.933	0.935	0.933	0.901

準確度 (AUC) 精確度 (Prec) 靈敏度 (Recall)


Compare models by: Area under ROC curve Negligible diff.: 0.1

Tree

Step 16 : 訓練與測試資料分離 (Train/Test Split)



Step 17 : 分類結果評估 Confusion Matrix (混淆矩陣)



Filter...

Data
Transform
Visualize
Model
Evaluate

Test and Score
Predictions
Feature as Predictor
Confusion Matrix
ROC Analysis
Performance Curve
Calibration Plot
Permutation Plot
Parameter Fitter


Unsupervised

Test and Score

Cross-validation accuracy estimation.

[more...](#)

Step 18 : 模型評估方法 : Test & Score (Test on Test Data)



Test and Score - Orange

☐ Cross validation
Number of folds: 5
☒ Stratified

☐ Cross validation by feature

☐ Random sampling
Repeat train/test: 20
Training set size: 66 %
☒ Stratified

☐ Leave one out

☐ Test on train data

☒ Test on test data

Evaluation results for target (None, show average over classes)

Model	AUC	CA	F1	Prec	Recall	MCC
Tree	0.943	0.911	0.911	0.915	0.911	0.866

Compare models by: Area under ROC curve
☐ Negligible diff.: 0.1

	Tree
Tree	

以訓練集訓練模型，並且將測試集代入模型測試。

Step 19 : 分類結果評估 Confusion Matrix (混淆矩陣)

Filter...

Data

Transform

Visualize

Model

Evaluate

Test and Score

Predictions

Feature as Predictor

Confusion Matrix

ROC Analysis

Performance Curve

Calibration Plot

Permutation Plot



Parameter Fitter

Unsupervised

Confusion Matrix

Display a confusion matrix constructed from the results of classifier evaluations.

[more...](#)



Step 20 : 將模型應用於新資料的預測 Predictions

Predictions

Display predictions of models for an input dataset.

[more...](#)

Predictions - Orange

Show probabilities for: Classes in data ☒ Show classification errors [Restore Original Order](#)

	Tree	error	iris	petal length	petal width	sepal length
1	1.00 : 0.00 : 0.00 → Iris-setosa	0.000	Iris-setosa	1.4	0.3	4.6
2	0.00 : 0.00 : 1.00 → Iris-virginica	0.000	Iris-virginica	5.5	2.1	6.8
3	0.00 : 0.00 : 1.00 → Iris-virginica	0.000	Iris-virginica	6.0	2.5	6.3
4	1.00 : 0.00 : 0.00 → Iris-setosa	0.000	Iris-setosa	1.3	0.2	4.7
5	0.00 : 0.97 : 0.03 → Iris-versicolor	0.032	Iris-versicolor	4.7	1.4	6.1
6	0.00 : 0.97 : 0.03 → Iris-versicolor	0.032	Iris-versicolor	4.6	1.5	6.5
7	0.00 : 0.97 : 0.03 → Iris-versicolor	0.968	Iris-virginica	4.8	1.8	6.2
8	0.00 : 0.97 : 0.03 → Iris-versicolor	0.032	Iris-versicolor	4.7	1.4	7.0
9	0.00 : 0.00 : 1.00 → Iris-virginica	0.000	Iris-virginica	5.3	2.3	6.4
10	1.00 : 0.00 : 0.00 → Iris-setosa	0.000	Iris-setosa	1.6	0.2	5.1

☒ Show performance scores Target class: (Average over classes)

Model	AUC	CA	F1	Prec	Recall	MCC
Tree	0.943	0.911	0.911	0.915	0.911	0.866

45 | 45 | 1x45

靈敏度
精確度
準確度

以 Data Sample 訓練模型，
並且模型未見過的 Remaining Data 代入模型測試。
先前我們設定 Data Sample 占比 70%，
因此 Remaining Data 有 $150 \times 30\% = 45$ 筆資料。

Step 21 : 分類結果評估 Confusion Matrix (混淆矩陣)

Filter...

Data

Transform

Visualize

Model

Evaluate

Test and Score

Predictions

Feature as Predictor

Confusion Matrix

ROC Analysis

Performance Curve

Calibration Plot

Permutation Plot



Parameter Fitter

Unsupervised

Confusion Matrix

Display a confusion matrix constructed from the results of classifier evaluations.

[more...](#)




從數據到決策：機器學習流程驗證與效益評估

以無程式碼分析重塑資料科學工作流，加速商業洞察

成果呈現


數據隱含規律的具象化



- 自動提取分類邏輯：以鳶尾花(Iris)數據集驗證，模型能成功從花瓣特徵中自動找出最佳決策邊界。
- 讓數據自己說話：系統直接產出高準確度(Accuracy 達 91.1%)的預測模型，捨棄耗時的人工規則推敲。

機器學習的核心思維

真正的預測力來自「泛化能力」



- 著眼未來，而非死記歷史：機器學習的重點不在於背誦已知的資料，而是面對「未知資料」時的預測與泛化能力。
- 客觀且嚴謹的驗證：透過 7:3 隨機抽樣與交叉驗證，確保模型在未見過的數據上依然精準，杜絕過度擬合(Overfitting)的現象。

商業效益

從「技術黑箱」到「透明決策」

```
from sklearn.model_selection import train_test_split


# 數據分割與模型建立
train = sklearn.datasets.load_iris(data=0)
from sklearn.model_selection import train_test_split
model = RandomForestClassifier()

# 模型訓練與驗證
model.fit(train, y_train)

# 模型預測與評估
score = model.score(test, y_test)
print(score)
```

傳統語法

大幅縮短時間



視覺化工作流

- 極速建置：零程式碼(No-code)拖曳式介面，免除繁複的語法除錯，只需傳統不到十分之一的建置時間。
- 跨域溝通：所見即所得的工作流程，讓技術模型直接轉化為非技術主管也能秒懂的「共通商業邏輯」。
- 專注核心：讓團隊將精力從「處理語法錯誤」釋放，100%投入於最高價值的商業策略決策。